



ANTI SMOG GUN



+91 7021994264



SALES@TRPMACHINES.COM



[HTTPS://TRPMACHINES.COM](https://trpmachines.com)

ANTI SMOG GUN

PARTICULAR'S NAME	COMPLETE DESCRIPTION
Moving	By Hand Manual
Mounted	By UCP Bearing, Heavy Structure
Usage/Application	Control Air Pollution For Dust Suppression At Construction Sites
Fan blade	8-10 Nos.
Fan Diameter	24 inches
Horizontal rotation Angle	340 Degree
Vertical Rotation	75-80 Degree Mechanical
Auto Rotate	Optional (If Required)
Water Pump Motor	2 HP CRI,
Blower Capacity	30000M ³ /Hr
Pump Warranty	1 Year From Lubi, CRI
Volume Flow	25-30 Ltr/Min
Water tank	1,000 Ltr
Frame Angle	50*5mm
Frame Sheet	14 Gauge
Drum Sheet	2-2.5mm
Elevation Angle	10°-60°
Blower RPM	2800
Main Motor For Fan	5 HP Crompton
Protection Level	65 IP
Isolation Valves	Ball & Globe Valve
Pump Location	Under Fog
Pump Specification	2.5M ³ @8 Bar
Water storage Tank Location	In-build Trolley
Material	MS Steel
Spraying Water Ring	Single Rings
Material of Water Ring	Stainless Steel 304
Electric power supply	415 V (Three Phase)
Equipment Type	Trolley mounted
Operational System	Control Panel with Transformer
Movable Tire	Wheel As per On Requirement
Mist spray nozzles	18 Nos.
Mist Nozzle Spec	Hollow Cone 2-3LPM@4-5Bar
Particle Size	20-150 micron
Nozzle Material	Brass Standard
Hose	High Pressure Rubber Hose Pipe, Oil Resistant Synthetic Rubber
Operating Panel	With Schneider Contactor, Relay Block
Best Price in MANUAL	1,40,000/-
Warranty	12 Months (Any Mfg Defects Only)
GST 18%	Extra
Installation/Trial	Free in Mumbai